



---

## TRRS Series



RADIATORE ELETTRICO AD OLIO  
OIL FILLED RADIATOR  
RADIATEUR ÉLECTRIQUE À BAIN D'HUILE  
ELEKTRISCHER ÖLRADIATOR  
OLIEGEVULDE ELEKTRISCHE RADIATOR  
RADIADOR ELÉCTRICO DE ACEITE  
RADIADOR ELÉTRICO A ÓLEO  
ΗΛΕΚΤΡΙΚΟ ΚΑΛΟΡΙΦΕΡ ΛΑΔΙΟΥ  
МАСЛЯНЫЙ ЭЛЕКТРИЧЕСКИЙ РАДИАТОР  
МАЙ ҚҰЙЫЛАТЫН РАДИАТОРЛАР  
ELEKTROMOS OLAJRADIÁTOR  
ELEKTRICKÝ OLEJOVÝ RADIÁTOR  
ELEKTRICKÝ RADIÁTOR NA OLEJ  
ELEKTRYCZNY GRZEJNIK OLEJOWY  
ELEKTRISK OLJERADIATOR  
OLJEFYLLD ELRADIATOR  
ELEKTRISK OLIERADIATOR  
ÖLJYTÄYTTENEN SÄHKÖPATTERI  
ULJNI RADIJATOR  
ELEKTRIČNI OLJNI RADIATOR  
МАСЛЕН РАДИАТОР  
RADIATOR ELECTRIC CU ULEI  
YAĞLI RADYATÖR  
إرشادات الاستعمال

---

**De'Longhi**

**IT**

pag. 4

**EN**

page 9

**FR**


page 13

**DE**

S.18

**NL**

pag. 23

**ES**

pág. 28

**PT**

pág. 33

**EL**

σελ. 38

**RU**

стр. 43

**KZ**

Бет. 48

**HU**

old. 54

**CS**

str. 59

**SK**

str. 63

**PL**

str. 67

**NO**

sid. 72

**SV**

sid. 76

**DA**

sid. 80

**FI**

siv. 84

**HR**

str. 88

**SL**

str. 92

**BG**

стр. 96

**RO**

pag. 101

**TR**

Sey. 105

**AR**

صفحة 2

## ELECTRICAL CONNECTION


- A) If your appliance comes fitted with a plug, it will incorporate a 13 Amp fuse. If it does not fit your socket, the plug should be cut off from the mains lead, and an appropriate plug fitted, as below. **WARNING:** Very carefully dispose of the cut off plug after removing the fuse: do not insert in a 13 Amp socket elsewhere in the house as this could cause a shock hazard. With alternative plugs not incorporating a fuse, the circuit must be protected by a 15 Amp fuse. If the plug is a moulded-on type, the fuse cover must be re-fitted when changing the fuse using a 13 Amp Asta approved fuse to BS 1362. In the event of losing the fuse cover, the plug must NOT be used until a replacement fuse cover can be obtained from your nearest electrical dealer. The colour of the correct replacement fuse cover is that as marked on the base of the plug.
- B) If your appliance is not fitted with a plug, please follow the instructions provided below:

**WARNING - THIS APPLIANCE MUST BE EARTHED**


### IMPORTANT

The wires in the mains lead are coloured in accordance with the following code:

Green and yellow:	Earth
Blue:	Neutral
Brown:	Live



As the colours of the wires in the mains lead may not correspond with the coloured markings identifying the terminals in your plug, proceed as follows:

The green and yellow wire must be connected to the terminal in the plug marked with the letter E or the earth symbol  or coloured green or green and yellow. The blue wire must be connected to the terminal marked with the letter N or coloured black. The brown wire must be connected to the terminal marked with the letter L or coloured red.

